

KOMO® Product certificate K91180/07





2022-07-01 Indefinite Valid until Dated

1 of 3 Page



Vulcanized rubber products for cold and hot non-drinking water applications M.O.L. ROMGUM Ławicki i Spółka Sp. J

STATEMENT BY KIWA

This product certificate is based on Guideline/BRL 2013 "Vulcanized rubber products for cold and hot nondrinking water applications" dated 12 October 2016 inclusive amendment sheet dated 10 October 2018, issued according to the Kiwa-Regulation for Certification.

The quality system and the product characteristics of this product are checked periodically. Based on this, Kiwa declares that there is legitimate confidence that:

Upon delivery, the product supplied by the certificate holder meets the requirements:

- Of the technical specifications laid down in this product certificate,
- The product requirements laid down both in this product certificate and in the Guideline/BRL.

Provided the vulcanized rubber products for cold and hot non-drinking water applications are accompanied by the KOMO® quality mark in the manner set out in this product certificate.

Ron Scheepers

Kiwa

This product certificate is also included on the KOMO foundation websites: www.komo.nl and www.komo-online.nl. Users of this product certificate is advised to check whether it is still valid. For this purpose consult the website of Kiwa: www.kiwa.nl.

Kiwa Nederland B.V. Sir Winston Churchilllaan 273 Postbus 70 2280 AB RIJSWIJK The Netherlands Tel. +31 88 998 44 00 Fax +31 88 998 44 20 NL.Kiwa.info@Kiwa.com www.kiwa.nl

Certificate holder M.O.L. ROMGUM Ławicki i Spółka Sp. J UI. Klonowa 13 62-002 SUCHY LAS Poland Tel. +48 (0)61 8125121

lab@mol-romgum.com.pl www.mol-romgum.com.pl/en



Assessed is:

- Quality system
- Product Periodic control

page 2 of 3

Vulcanized rubber products for cold and hot non-drinking water applications

TECHNICAL SPECIFICATION

Vulcanized rubber products for cold and hot non-drinking water applications

Product characteristics

The products as specified in the table below fulfil the requirements of BRL-2013 for the mentioned class(es).

Specification

Rubber Compound:	EPDM EP60-T						
Hardness:	60 IRHD	Field of applicati	on ² : I – WC			Remarks:	
Ozone Class ¹ :	1	Production meth	od:	Injection m	olding		
*	Seal type	Tegra 600		7	Seal ty	/ре	Tegra 800
	Nominal Dimensions	586 mm			Nominal Dimensions		894 mm
	Cross Sections	4 – 12,6 mm			Cross Sectio	ns	12,5 – 43.mm
	Seal type	O-ring			Seal ty	/pe	
	Nominal Dimensions	405 mm			Nominal Dimensions		
	Cross Sections	14 mm			Cross Sectio	ns	
Rubber Compound:	EPDM EP70						
Hardness:	70 IRHD	Field of applicati	on ² : I – WC			Remarks:	
Ozone Class ¹ :	1	Production meth	od: Injection me		olding		
1	Seal type	Tegra 1000					
	Nominal Dimensions	965 mm					
	Cross Sections	6 – 36,9 mm					

- 1 Ozone resistance class according to BRL-2013:
 - For products with a high risk of attack by ozone, for instance in case of separately supplied products without sufficient packaging or in case of connections with preinstalled rubbers under strain;
 - II For products for which a normal resistance to ozone is required;
 - III For rubbers which are never (partly) exposed to the open air when they are in tension. Transport shall always take place in sealed packages.
- 2 Field of application class according to BRL 2013 class:
 - Cold water supply at temperatures continuously up to 45 °C and intermittently up to 95 °C;
 - II Hot water supply at temperatures intermittently up to 110 °C, or water supply up to 110 °C in serviceable piping systems;
 - III Hot water circulation systems based on the classification class 2 in ISO 10508;
 - IV District heating, secondary systems with hot water circulation between 75 °C and 95 °C.

Field of application class according to EN 681-1:

WC As in BRL-2013 class I; WD As in BRL-2013 class II;

WF As in BRL-2013 class II, for IIR-copolymer; WG As in BRL-2013 class I, oil resistance.

Details of the products are included in the drawing list, which forms a part of the IQC schedule.

Kiwa authenticates this list. A copy of this list can be obtained from the producer.



KOMO® Product certificate

page 3 of 3

Vulcanized rubber products for cold and hot non-drinking water applications

Marking

The following marks and indications must be provided on each product* and product packaging in a clear, legible and indelible way:

- · the name of manufacturer or the deposited trade mark;
- KOMO (or KOMO® word mark) with certificate number;
- the nominal dimension or dimensions;
- the nominal hardness;
- the year of manufacturing and preferably the quarter;
- type of rubber applied by means of the letter codes of the nomenclature according to ISO 1629;
- the application class (I, II, III or IV);
- on products from blends, the letter B ("blend") shall be placed behind the first letter code;
- the ozone resistance class ("Ozone I, II or III"). For rubber rings made from two compounds the compound with the lowest class is valid.
- · BRL number and certificate number; optional
- # If the dimensions of the products are such that the indications applied to them may impair the product, the products may be marked per package in consultation with the manufacturer, the buyer and Kiwa. Products produced by cutting or die cutting out of sheets may be marked per package.

RECOMMENDATION FOR THE CUSTOMER

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

if you should reject a delivery on the basis of the above, please contact:

- M.O.L. ROMGUM Ławicki i Spółka Sp. J
- and, if necessary:
- Kiwa Nederland B.V.

For the proper storage, transport and processing consult the instructions of the certificate holder.

The statements in this product certificate may not be used to replace the CE marking and/or the corresponding mandatory Declaration of Performance.

